



High Performance GPS Surveillance & Tracking

- High sensitivity GPS integrated for operation in difficult, low signal strength environments.
- GSM/GPRS tri-band communications for economical global operation.
- Rechargeable internal battery enables extended long term operation, with no requirement to replace batteries.
- Very compact and easily installed, with self-contained antennas for zero installation costs and high reliability.
- All included in one box, including multi-function magnetic mount and mains charger.
- May be permanently powered by connection to vehicle power via an optional vehicle charger.

Ocellus S100 is a High Sensitivity GPS/GPRS remote surveillance and tracking device, which allows users to monitor the location of vehicles and assets of all kinds. High Sensitivity GPS enables operation in urban canyons, under heavy foliage and even indoors, and permits installation in locations where a direct sky view is not available. It is particularly suitable for operation in and under vehicles.

Its internal activity sensor enables power-saving by allowing the unit to power down in between position fixes, contributing to its exceptional battery life.



Ocellus S100

Attachment to any tracking subject is simple because of its small size (133 x 48 x 25 mm) and removable multifunction magnetic mount.

The integrated antennas and battery make the unit highly reliable by removing the need for a complex wiring installation. With its High Sensitivity GPS, sophisticated power management and integrated tri-band GSM/GPRS module, the Ocellus S100 enables users to both enhance existing telematics applications and enable new business concepts to be realised.

Data Sheet

Applications

- Covert Surveillance – rapidly attachable to targets, and capable of tracking in difficult environments, eg. Under a vehicle.
- Fleet Management – may be installed temporarily or permanently to any vehicle, either self-powered from its internal rechargeable battery, or powered via one of two optional vehicle chargers,.
- Asset Tracking – may be used to track valuable goods in the supply chain.
- Theft Prevention – use S100 to monitor the position of valuable items like vehicles, caravans, temporary buildings, boats etc. for extended periods.

Configuration Settings

Ocellus S100 is remotely configurable to suit the user's requirements, through a web enabled QinetiQ mapping interface, or tracking services provided by third parties.

Reporting frequency, alert thresholds, positioning variables and numerous other parameters are easily configurable, enabling Ocellus S100 to support a wide variety of tracking requirements. The following parameters are all remotely configurable:

Device Settings

- LED Indicators, Covert Mode – Ocellus may be configured to have LED indicators at 'full brightness', turned 'off' for covert deployment, or set on 'dim' in order to limit distraction, eg. When fitted inside a vehicle.

- GPS Throttle – a configurable setting that defines how hard the GPS engine should work to obtain a position fix, enabling the user to prioritise between extended battery life and improved position accuracy.
- Motion Sensor Sensitivity – permits the setting of the time period over which the motion sensor should detect motion in order for Ocellus to interpret disturbance as motion, thus avoiding false alarms.
- GPRS and SMS Credit – supports the limiting of number of reports the unit is permitted to send over either GPRS or SMS, enabling low cost operation over GPRS, or capping tracking expenditure.



Position Reports

S100 may be configured to provide any combination of the following report types:

- Moving - while in motion (with reporting intervals configured as required).
- Periodic - while stationary (with reporting intervals configured as required), e.g. for 'confidence' reports.
- Go - when a unit starts to move.
- Stop - when a unit stops moving.

Data Sheet

Additional Parameters Available With Reports

- Altitude
- Speed
- Horizontal and Vertical Accuracy Estimates
- Course Over Ground – provides heading information, enabling the direction of travel to be interpreted by the tracking service provider (eg. To show a direction arrow on the map).
- Battery % Remaining – allows remote monitoring of the unit's battery condition. Also allows the tracking service provider to send the user an alert if the battery level drops below a pre-set level.
- Report Interval (ie how long since the last report).
- Seconds in Motion - since the last report.
- Initial and Remaining Credits of Position Reports over SMS and GPRS – enables the user to check at a glance how report credits have reduced, to calculate the cost of operation.

Geofencing

- Geofencing is enabled by the web tracking services which support Ocellus.

Alarms

- Alarms are alerts sent to the user by the tracking service. These can be created by the tracking service provider, based on information provided by Ocellus. Examples include geofence breaches and 'battery low' alarms.

GSM Frequencies Supported

Ocellus S100 is available in two tri-band variants:

- S100e supports the 900 and 1800MHz frequencies used in Europe, Asia and most of the world outside the American continent, and additionally provides the 1900MHz band for roaming in the Americas.
- S100u supports the 850 and 1900MHz frequencies used in the USA and most of the American continent, and provides support for the 1800MHz band for roaming in Europe and the rest of the world.



Data Sheet

Ocellus S100 Specification

GPS PERFORMANCE (12 CHANNEL)	RF Reception Sensitivity:	-186 dBW tracking -184 dBW acquisition		
	Signal Acquisition	Hot:	<1 sec	
		Warm:	<38 sec	
		Cold:	<45 sec	
	Re-acquisition		<0.5 sec	
ACCURACY	Position: Outdoor/Indoor Velocity (Outdoor):	<5m / <50m typical <0.05ms ⁻¹		
GSM/GPRS PERFORMANCE	Tri-band GSM/GPRS: GPRS Class 10: Point-to-point SMS: Text and PDU mode SMS GSM phase 2/2+ compliant Output Power - GSM900 Output Power - GSM1800/1900	900/ 1800/ 1900 MHz Max 85.6 kbps MO and MT 2W 1W		
POSITION FIXES STORED	(In Internal Memory)	Up to 4,000 positions		
PHYSICAL	Ocellus S100 Dimensions: Weight: Ocellus Case: Multifunction Mount: Multifunction Mount Dimms:	133mm (L) x 48mm (W) x 24mm (H) 141g All plastic Anodised aluminium, incorporating 4 magnets 90mm (L) x 80mm (W) x 6mm (H)		
ENVIRONMENTAL	Operating / Storage Temp: Max Velocity / Altitude: Max Acceleration / Jerk: Dust / Water Ingress Protection:	-20°C to + 60°C / -45°C to + 85°C 515 ms ⁻¹ / 18,000m Complies with DEF STAN 0 0-35 (Part 3) IP56		
POWER	Internal Battery Charging Requirements: Mains Charger:	Lithium Polymer 5V, 600mA 5V, 1000mA output, 110 – 240V, 50-60Hz AC input, supplied with Euro, UK, US and Australian adapters		
POWER EFFICIENCY	Number of Positions Reported (on one battery charge) - Outdoors: - Inside a vehicle, e.g. glove box - Under a vehicle	Reporting Once /Day	Reporting 10 Times/Day	Reporting 100 Times/Day
		200* 150* 100*	500* 400* 200*	600* 500* 350*
		* Depending on installation conditions; these figures are for guidance only.		
ALARMS	Battery Low, Geo-Fencing	Enabled by web tracking service		
INTERFACES	On/Off Switch: Status Indicator LEDs x 4: Battery Charging Port: Web Interface:	Activates / de-activates the unit Status monitoring Enables battery charging Enables remote monitoring and configuration of Ocellus over the web		
ACCESSORIES	5V Universal Mains Charger: Multifunction Mount Assembly: Vehicle Charger (6-32V input): In-Line Vehicle Charger (6-32V):	Part No. QP002 0-248 (supplied with S100) Part No. QP002 0-100 (supplied with S100) Part No. QP100 7-128 Part No. QP100 7-129		

This specification is subject to change without notice.

For more information please contact:

Foretrack

35 City Industrial Park, Southern Road, Southampton, Hampshire, SO15 1HG

Tel: 02380 718700

E-mail: sales@foretrack.co.uk

Fax: 02380 718770

Web: www.foretrack.co.uk

